

# Cutting tools

## SUPERCUT XPM



**flextos GmbH** | Rosenheimer Straße 44 | 83064 Raubling | Germany

Phone +49 (8031) 233 88 60 | Fax +49 (8031) 233 88 68 | [info@flextos.com](mailto:info@flextos.com) | [www.flextos.com](http://www.flextos.com)

Managing Director: Stefan Velkoski

Registration Office: Traunstein | HRB: HRB 264 15 | USt-IdNr./VAT No: DE 314200950

**TPEF.00.00.0083**                      profile cutter D3 S8 T12.5

profile cutter; cutting depth up to 12.5 mm; cutting diameter 3 mm; shaft 8 mm



**WPCM.00.00.0004**                      profile cutter D6 S8 T12.5

profile cutter; cutting depth up to 12.5 mm; cutting diameter 6 mm; shaft 8 mm



**WPCM.00.00.0002**                      profile cutter D6 S8 T16

profile cutter; cutting depth up to 16 mm; cutting diameter 6 mm; shaft 8 mm



**WPCM.00.00.0003**                      profile cutter D6 S8 T25

profile cutter; cutting depth up to 25 mm; cutting diameter 6 mm; shaft 8 mm



**WPWE.00.00.0038**                      groove cutter D8 S8 T20

Groove cutter for grooving in plasterboard and other board materials; groove width 8 mm; shank 8 mm; max. groove depth 20 mm



**WSVG.00.00.0005**                      v-groove cutter 45° S8 T17

v-groove cutter for 45° angles; cutting depth up to 17 mm; shaft 8 mm



**WSVG.00.00.0014**                      special v-groove cutter 45°(i) S8 T11

special v-groove cutter for 45° interior corners/angles; cutting depth up to 11 mm; shaft 8 mm



**WPWE.00.00.0021** special v-groove cutter 45°(i) S8 T16

special v-groove cutter for 45° interior corners/angles; cutting depth up to 16 mm; for inside edges; shaft 8 mm



**WSVG.00.00.0003** v-groove cutter 60° S8 T17

v-groove cutter for 60° angles; cutting depth up to 17 mm; shaft 8 mm



**WPWE.00.00.0001** v-groove cutter for reinforced edges

v-groove cutter for reinforced, rounded 90° edges/angles; radius 2 mm; shaft 8 mm



**WSVG.00.00.0009** v-groove cutter 90° S8 T18.5

v-groove cutter for 90° angles; cutting depth up to 18.5 mm; special cut 90.2°; shaft 8 mm



**WPWE.00.00.0017** v-groove cutter DIA 90° S8 T15

v-groove cutter DIA; for 90° angles; cutting depth up to 15 mm; diamond-tipped; shaft 8 mm



**WPWE.00.00.0022** special v-groove cutter 90°(i) S8 T11

special v-groove cutter for 90° interior corners/angles; cutting depth up to 11 mm; shaft 8 mm



**WPWE.00.00.0023** special v-groove cutter 90°(i) S8 T16

special v-groove cutter for 90° interior corners/angles; cutting depth up to 16 mm; shaft 8 mm



**TPEF.00.00.0081** flute milling cutter D25 S8

flute milling cutter;  $\varnothing$  25 mm; shaft 8 mm



WPWE.00.00.0005 flute milling cutter D20 S8

flute milling cutter;  $\varnothing$  20 mm; shaft 8 mm



8604.30.00.1003 multi-blade sawing kit XPM

set of 4 sawblades for slotted boards



WSSB.01.30.0180 saw blade, standard 180mm

saw blade,  $\varnothing$  180 mm; 30 teeth; 180 x 2.8/1.8 x 20 mm  
for SUPERCUT XPM Standard and 2.3kW saw unit SUPERCUT XPS + CNC



WSSB.00.30.0180 saw blade, XPM multi-blade

saw blade, multi-blade XPM;  $\varnothing$  180 mm; 30 teeth; 180 x 2.0/1.2 x 30 mm



WSSB.00.10.0180 saw blade, XPM DIA

sawblade, DIA XPM;  $\varnothing$  180 mm; 10 teeth; 180 x 2.4/1.8 x 20 mm

